



Special Conditions

Stains on Pre-Fixx protected vinyl wallcoverings can be cleaned by the following methods (Staining agents have been grouped to allow quick reference for cleaning instructions):

Cleaning Agents to Use:

1. Full Strength household cleaners (non-abrasive type) to be used with water and scrub brush
 - 409 All Purpose Cleaner*
 - Fantastic*
 - Butchers Sun Bath Cleaners*
 - Service Master's Wallgide Plus*
 - Other type household cleaners and bleaches*
2. Solvent type cleaner to be used with scrub brush and cloth. For most effective cleaning, use 100% full strength with brush. Dry area with cloth.
 - Rubbing Alcohol (IPA type)*
 - Service Master's Disaster Clean*
 - Mineral Spirits*
 - Kerosene*
 - Naptha (lighter fluid)*
 - Turpentine (paint thinner)*
3. Strong active solvent cleaners such as nail polish remover (acetone/water) with scrub brush and cloth.

Co-Polymer

To clean co-polymer, dust it with a soft, damp cloth or chamois and wipe the surface gently. Use soap and lukewarm water to remove light dirt. After washing and rinsing, be sure to dry the surface by blotting with a damp cloth or chamois. If a cleaner must be used to remove heavier dirt, please try one of the following recommended cleaners:

- | | |
|------------------------|---|
| • Top Job with Ammonia | • Janitor in a Drum |
| • Fantastik | • Cascade |
| • Swish Detergent | • Joy Detergent |
| • Spic & Span | • Handy Andy |
| • Mr. Clean | • All Detergent (Powder) |
| • Clagonite | • Isopropanol (45%) – higher |
| • Johnson's Pledge | concentrations will dull the firm surface |

Be careful to avoid getting cleaning solution on the fiberglass core. It is best to apply all cleaners to the cloth or chamois and not directly on the perforated co-polymer surface.

Painted Panels

G&S Acoustics' Painted Panels should be cleaned using the following methods:

- Use compressed air to lightly blow off any debris
- Use a dry cloth or soft bristle brush, such as a feather duster, to wipe away debris

Small Paint Repair Instructions

For small areas where paint is chipped, use a small brush and lightly touch-up the spot with paint supplied by G&S Acoustics.

Large Paint Repair Instructions

For large areas requiring new paint, spray the face of the panel only with new paint. Do not roll or brush on paint.

type cleaning preparations such as nail polish remover, tar and bug removers, etc., can be used with Pre-Fixx protected wallcoverings to remove residual stains that remain after cleaning with standard cleaning agents.