



SHERWIN-WILLIAMS

Care and Cleaning of Interior and Exterior Coatings

Background:

Establish procedures to maintain and clean interior and exterior painted substrates. To assure maximum washability and durability, wait at least two weeks before washing the dry paint film. Exterior coatings typically are very soft and flexible to allow for expansion and contraction of the coating during changes of temperature. Any hard scrubbing of standard exterior coatings is likely to damage the film. To clean and maintain the interior and exterior surfaces, we recommend these procedures.

Concentrated Cleaners, Liquid or Dry:

- Read all the package directions before using. It is always recommended to test any cleaner on a small, inconspicuous area prior to use.
- Mix or dilute the cleaner per package instructions. Solution strength may be adjusted depending on amount and type of soil.
- Remove any heavy debris and contaminants.
- Using a sponge or cloth, wash surface dirt and marks.
- Do not allow the cleaner to dry on the surface.
- Always clean from the bottom of a wall to the top.
- Rinse the surface thoroughly.
- Repeat if necessary.

Premixed Spray Cleaners:

- Read all the package directions before using. It is always recommended to test any cleaner on a small, inconspicuous area prior to use.
- Turn spray nozzle to desired spray pattern. (Open with nozzle facing away from you.)
- Remove any heavy debris and contaminants.
- Apply the cleaner to the dirt and marks; apply just enough to wet the area.
- Using a damp sponge or cloth, wipe to remove the surface dirt and marks and any excess cleaner. For difficult stains, some scrubbing may be necessary.
- Do not allow the cleaner to dry on the surface.
- If recommended on the cleaner package, rinse the surface thoroughly.
- Repeat if necessary.
- Return spray nozzle to the closed position.

Cautions:

- Thoroughly read and understand all the label cautions prior to using any cleaner.
- Be sure that the cleaner is appropriate for the dirt/contamination.
- Do not mix together any cleaning compounds containing bleach and ammonia.
- Abrasive cleansers may damage a paint film, use very carefully.
- Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions would be advised.

WARNING!

- Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.



SHERWIN-WILLIAMS®

Care and Cleaning of Interior and Exterior Coatings

The Sherwin-Williams Company Cleaning Products

SuperDeck® Deck Wash is designed to bring back the fresh, natural look of your deck. Enjoy the self-working, no scrub formulation. This product is an excellent choice to restore your surface or to use as a pretreatment for staining, preserving, or sealing. Use on decks and outdoor furniture made of pressure treated wood, cedar, pine, and most other woods. This product is intended for exterior use only.

SuperDeck® Stain & Sealer Remover is specifically designed to remove most semi-transparent and weathered solid latex and oil-based stains from decks and other exterior wood. SuperDeck Stain & Sealer Remover allows you to change the color of your deck or siding by restoring the natural beauty of the wood. SuperDeck Stain & Sealer Remover can be used on most exterior wood surfaces such as decks, siding and fences and will remove the following stains and finishes:

- Polyurethane and some weathered latex paint.
- Oil-based toners, semi-transparent, and weathered solid stains.
- Water-based toners, semi-transparent, and weathered stain.
- Water-reducible toners, semi-transparent and weathered solid stains.
- Old, weathered, clear protective finishes.

SuperDeck Stain & Sealer Remover will restore color to severely weathered and discolored wood.

SuperDeck® Revive® Deck & Siding Brightener is a fast-acting, ready-to-use cleaner specially formulated for cedar, redwood and other highly resinous exterior woods as well as dense woods such as mahogany. Due to the chemical characteristics of these types of woods, traditional cleaners can leave the surface with an unnatural, darkened appearance. SuperDeck Revive Deck & Siding Brightener will help remove dirt and unsightly stains caused by mildew and algae, gray and weathered wood, tannin bleed and nail bleed as well as stubborn mill glaze (a surface barrier to wood coatings found on most newly installed cedar and redwood) and restore the surface to its bright, clean natural look. SuperDeck Revive Deck & Siding Brightener can be used on any new or existing exterior structure including wood decks, fences, siding, shakes, shingles, boat docks, boardwalks, outdoor furniture, picnic tables, hot tubs, planters, benches, trellises and gazebos.

H&C Concrete Etching Solution is a phosphoric acid-based etcher that has been developed to acid etch concrete surfaces before applying H&C Silicone Acrylic Concrete Sealer, H&C Shield Plus Concrete Stain, and other coatings. Uses: • Basement floors and walls • Garage floors, carports and driveways • Porches, patios, walkways, steps • Swimming pool aprons • Recreation areas • Parking structures and parking lots • Retaining walls • Containment areas • Tilt-up construction • Removes efflorescence (alkali salts) • Reduces the pH of new concrete and new mortar joints.

H&C Degreaser is a concentrated heavy-duty cleaner that will remove most automotive fluids (oil, grease, brake fluid, transmission fluid, gear fluid and antifreeze) from concrete and masonry surfaces. Its primary use is to degrease and prepare concrete, block, brick, and masonry. Features: • Removes grease and oil stains • Prepares surfaces for paints, stains, and sealers • Increases any coating's ability to bond with the surface by providing a clean substrate Recommended Uses: • Stadium Supports • Bridges and Bridge Structures • Parking Garages • Patios and Walkways • Pool Decks • Concrete Driveways • Garage Floors • Block & Stucco Walls • Athletic/Tennis/Shuffleboard Courts • Other Concrete Surfaces • Use prior to etching