



SEALANT USED
AT TERMINATION

DOES THIS
FLASHING NEED
TO LAP ONTO
WALL?

FILL CELLS
SOLID

PAN SET IN BED
OF SEALANT

GROUTED SOLID
BENEATH
FLASHING



GRACE
situr

JOINTS WELDED





5 BEADS OF
SEALANT AT LAP

5 BEADS OF
SEALANT AT LAP





SELF ADHERED
FLASHING AT
LAPS - 3"
OVERLAP ON
EACH SIDE OF
JOINT

NEEDS SELF
ADHERED
FLASHING AT
WELD PER 042000
2.7D




SELF ADHERED
FLASHING AT
END DAM. CAN
NOT RUN ENTIRE
3" DUE TO
HEIGHT OF END
DAM.

INSTALL
TERMINATION
BAR AND USE
BERRIBOND AT
TOP OF
FLASHING



PERFORM
WATER TEST AT
LAP JOINTS FOR
30 MINS.





INCORRECT
INSULATION -
USE FIBERGLASS
FACE

CORRECT WALL
TIES

WEEPS
INSTALLED

1/4" MAX

OVERLAP
FLASHING
PIECES - DO NOT
TRIM DRIP EDGE

CURRENT
FLASHING
OVERHANG - DO
NOT EXCEED 1/4"



IS THIS
FLASHING
OVERHANG
ACCEPTABLE?

