



GENERAL DESCRIPTION

A general purpose, synthetic polymer based contact bonding adhesive.

BASIC USE

Specifically designed to bond Hydrotech's Flex-Flash UN (uncured neoprene) flashing membrane to an acceptable substrate (i.e. wood, metal, concrete).

ADVANTAGES

- High resistance to aging, heat and cold
- Long tack time for easy construction assembly

TECHNICAL SPECIFICATIONS

Color:	Amber (yellow)	Weight/Gallon:	7.05 lb
Solvents:	Acetone	Solids Content:	24-25%
	Textile Spirits	Specific Gravity:	0.845
	Xylol	Shelf Life:	9 months, unopened
Base:	Neoprene Polymers		

APPLICATION

- Stir the Bonding Adhesive thoroughly before and during use.
- The mating surfaces of the Flex-Flash UN and substrate must be clean and free of any contaminants.
- Apply the Bonding Adhesive with a brush or roller. Coat both surfaces completely and evenly, avoiding globs and puddles, at a rate of 60 square feet per gallon on each surface.
- Allow both membrane surfaces to dry, typically 20-30 minutes depending on ambient temperature and humidity. When adequately dry the Bonding Adhesive should not stick or string-up to a dry finger touch.
- Mate the coated surfaces and apply positive pressure with a steel hand roller or broom to insure 100% adhesion.
- The minimum recommended application temperature is 40 °F or higher.

CAUTIONS

FLAMMABLE LIQUID!

Do not use near open fire or flame and extinguish all smoking materials. Use only in well ventilated areas. Avoid prolonged breathing of vapors and contact with skin.

A Material Safety Data Sheet is available upon request.



WESTERNTM

SPECIALTY CONTRACTORS
CONFIDENCE THROUGH PERFORMANCE

1947 Gravois Avenue
St .Louis, MO 63104
Phone: (314) 773-8813 Fax: (314)773-0843

TO: Paric Corporation

LETTER OF TRANSMITTAL

DATE	JOB
2-Dec-16	Webster U ISB
ATTENTION	
Devin Gates	
Re: Waterproofing Submittals	

We are Sending You

- | | | | |
|--|--|--|--|
| ☒ Submittals | ☐ Lien waiver | ☐ Signed change order | ☐ Insurance Certificate |
| ☐ Quotation | ☐ Signed contract | ☐ Change order request | ☐ Invoice |
| ☐ Copy of Letter | ☐ Warranty | ☐ Request for information | |
| ☐ Other _____ | | | |

Copies	Date	Description
1		Hydrotech 6125 Membrane (2 pgs)
1		Hydrotech Surface Conditioner (1 pg)
1		Hydrotech Flex Flash - F (1 pg)
1		Hydrotech Flex Flash - UN (1 pg)
1		Hydrotech 30 Protection Board (1 pg)
1		Hydrotech Bonding Adhesive (1 pg)
1		Hydrotech Lap Sealant (1 pg)
1		Hydrotech Splice Cement (1 pg)
1		DOW PLAZAMATE Insulation Panels (2 pgs)
1		Filter Fabric (1 pg)
1		Sketch Sheets of Areas Receiving waterproofing and paver system (paver layout inc.) (2 pgs)
1		Hydrotech Flex-Flash Typical Flashing Details (4 pgs)

THESE ARE TRANSMITTED as checked below:

- ☒ For approval
- ☐ For your use
- ☐ As requested
- ☐ For review and comment
- ☐ FOR BIDS DUE



REMARKS:

PAVER SAMPLES AND COLORS ARE ONSITE.....Let me know if you should need anything else.

Copy: File

Signed: Thomas J Belgeri / Dept Mgr - StL 01