



to use with uncured
flashing work

GENERAL DESCRIPTION

A general purpose, synthetic polymer based contact bonding adhesive.

BASIC USE

Specifically designed to bond Hydrotech's Flex-Flash UN (uncured neoprene) flashing membrane to an acceptable substrate (i.e. wood, metal, concrete).

ADVANTAGES

- High resistance to aging, heat and cold
- Long tack time for easy construction assembly

TECHNICAL SPECIFICATIONS

Color:	Amber (yellow)	Weight/Gallon:	7.05 lb
Solvents:	Acetone	Solids Content:	24-25%
	Textile Spirits	Specific Gravity:	0.845
	Xylol	Shelf Life:	9 months, unopened
Base:	Neoprene Polymers		

APPLICATION

- Stir the Bonding Adhesive thoroughly before and during use.
- The mating surfaces of the Flex-Flash UN and substrate must be clean and free of any contaminants.
- Apply the Bonding Adhesive with a brush or roller. Coat both surfaces completely and evenly, avoiding globs and puddles, at a rate of 60 square feet per gallon on each surface.
- Allow both membrane surfaces to dry, typically 20-30 minutes depending on ambient temperature and humidity. When adequately dry the Bonding Adhesive should not stick or string-up to a dry finger touch.
- Mate the coated surfaces and apply positive pressure with a steel hand roller or broom to insure 100% adhesion.
- The minimum recommended application temperature is 40 °F or higher.

CAUTIONS

FLAMMABLE LIQUID!

Do not use near open fire or flame and extinguish all smoking materials. Use only in well ventilated areas. Avoid prolonged breathing of vapors and contact with skin.

A Material Safety Data Sheet is available upon request.



77 Westport Plaza
Suite 250
St. Louis, MO 63146

TRANSMITTAL

No. 15051-0347

Paric Corporation

PROJECT: 15051-Webster University Interdisciplinary Science Building

DATE: 11/29/2016

TO: Cannon Design
1100 Clark Ave
St Louis MO 63102

Fax;
314-241-2203

RE: Hot Fluid Applied Waterproofing at Pavers
Product Data

ATTN: Kelvin Patel

JOB: 15051

WE ARE SENDING:	SUBMITTED FOR:	ACTION TAKEN:
☐ Shop Drawings	☒ Approval	☐ Approved as Submitted
☐ Letter	☐ Your Use	☐ Approved as Noted
☐ Prints	☐ As Requested	☐ Returned After Loan
☐ Change Order	☐ Review and Comment	☐ Resubmit
☐ Plans		☐ Submit
☐ Samples	SENT VIA:	☐ Returned
☐ Specifications	☐ Attached	☐ Returned for Corrections
☒ Other: Product Data	☐ Separate Cover Via:	☐ Due Date:

Item	Package	Code	Rev.	Copies	Date	Description	Status
Submittal		071413-007	1		11/29/2016	Hot Fluid Applied Waterproofing at Pavers Product Data	Submitted

NOTES:

CC:

Signed: _____
Devin Gates