



to use with uncured
flashing work

GENERAL DESCRIPTION

A one-part, synthetic polymer based, aliphatic solvent lap seam sealant.

BASIC USE

Specifically designed to caulk and seal the exposed sheet edges of Hydrotech's Flex-Flash UN (uncured neoprene) flashing membrane.

ADVANTAGES

- Good adhesion to neoprene membranes as well as metal, wood and concrete
- Excellent resistance to ozone, ultra-violet and general weathering
- Excellent low temperature resistance

TECHNICAL SPECIFICATIONS

Color:	Black	Weight/Gallon:	9.31 lb
Solvents:	Mineral Spirits	Solids Content:	66.4%
Base:	E.P.D.M. Rubber	Specific Gravity:	1.116
		Shelf Life:	9 months, unopened

APPLICATION

- The flashing membrane sheet edge and immediate surrounding area should be clean and free of all contaminants (dirt, oil, water) as well as any excess Splicing Cement from the lap/seam.
- Apply a bead of Lap Sealant (approx. 3/8 inch) over the membrane sheet edge and "feather" the sealant so that it meets the membrane surfaces smoothly.
- The minimum recommended application temperature is 40 °F or higher.

CAUTIONS

FLAMMABLE LIQUID!

Do not use near open fire or flame and extinguish all smoking materials. Use only in well ventilated areas. Avoid prolonged breathing of vapors and contact with skin.

A Material Safety Data Sheet is available upon request.



77 Westport Plaza
Suite 250
St. Louis, MO 63146

TRANSMITTAL

No. 15051-0347

Paric Corporation

PROJECT: 15051-Webster University Interdisciplinary Science Building

DATE: 11/29/2016

TO: Cannon Design
1100 Clark Ave
St Louis MO 63102

Fax;
314-241-2203

RE: Hot Fluid Applied Waterproofing at Pavers
Product Data

ATTN: Kelvin Patel

JOB: 15051

WE ARE SENDING:	SUBMITTED FOR:	ACTION TAKEN:
☐ Shop Drawings	☒ Approval	☐ Approved as Submitted
☐ Letter	☐ Your Use	☐ Approved as Noted
☐ Prints	☐ As Requested	☐ Returned After Loan
☐ Change Order	☐ Review and Comment	☐ Resubmit
☐ Plans		☐ Submit
☐ Samples	SENT VIA:	☐ Returned
☐ Specifications	☐ Attached	☐ Returned for Corrections
☒ Other: Product Data	☐ Separate Cover Via:	☐ Due Date:

Item	Package	Code	Rev.	Copies	Date	Description	Status
Submittal		071413-007	1		11/29/2016	Hot Fluid Applied Waterproofing at Pavers Product Data	Submitted

NOTES:

CC:

Signed: _____
Devin Gates