



GENERAL DESCRIPTION

A synthetic polymer based lap splicing cement.

BASIC USE

Specifically designed to bond Hydrotech's Flex-Flash UN (uncured neoprene) flashing membrane together.

ADVANTAGES

- High resistance to aging, heat and cold
- One-part system
- Long tack time for easy construction assembly

TECHNICAL SPECIFICATIONS

Color:	Black	Weight/Gallon:	7.3 lb
Solvents:	Toluene	Solids Content:	26-33%
	Hexane	Specific Gravity:	0.87
	Xylene	Shelf Life:	9 months, unopened
Base:	Synthetic Polymers		

APPLICATION

- Stir the Splicing Cement thoroughly before and during use.
- The mating surfaces of the Flex-Flash UN must be clean and free of any contaminants. The polyethylene release sheet should be removed from the Flex-Flash UN.
- Apply the Splicing Cement with a brush or roller. Coat both surfaces completely and evenly, avoiding globs and puddles, at a rate of 60 square feet per gallon on each surface.
- Allow both membrane surfaces to dry, typically 20-30 minutes depending on ambient temperature and humidity. When adequately dry the Splicing Cement should not stick or string-up to a dry finger touch.
- Mate the coated membrane surfaces and apply positive pressure toward the outside of the lap with a steel hand roller.
- Seal the exposed membrane sheet edge with Hydrotech's Lap Sealant.
- The minimum recommended application temperature is 40 °F or higher.

CAUTIONS

FLAMMABLE LIQUID!

Do not use near open fire or flame and extinguish all smoking materials. Use only in well ventilated areas. Avoid prolonged breathing of vapors and contact with skin.

A Material Safety Data Sheet is available upon request.



WESTERNTM

SPECIALTY CONTRACTORS
CONFIDENCE THROUGH PERFORMANCE

1947 Gravois Avenue
St .Louis, MO 63104
Phone: (314) 773-8813 Fax: (314)773-0843

TO: Paric Corporation

LETTER OF TRANSMITTAL

DATE	JOB
2-Dec-16	Webster U ISB
ATTENTION	
Devin Gates	
Re: Waterproofing Submittals	

We are Sending You

- | | | | |
|--|--|--|--|
| ☒ Submittals | ☐ Lien waiver | ☐ Signed change order | ☐ Insurance Certificate |
| ☐ Quotation | ☐ Signed contract | ☐ Change order request | ☐ Invoice |
| ☐ Copy of Letter | ☐ Warranty | ☐ Request for information | |
| ☐ Other _____ | | | |

Copies	Date	Description
1		Hydrotech 6125 Membrane (2 pgs)
1		Hydrotech Surface Conditioner (1 pg)
1		Hydrotech Flex Flash - F (1 pg)
1		Hydrotech Flex Flash - UN (1 pg)
1		Hydrotech 30 Protection Board (1 pg)
1		Hydrotech Bonding Adhesive (1 pg)
1		Hydrotech Lap Sealant (1 pg)
1		Hydrotech Splice Cement (1 pg)
1		DOW PLAZAMATE Insulation Panels (2 pgs)
1		Filter Fabric (1 pg)
1		Sketch Sheets of Areas Receiving waterproofing and paver system (paver layout inc.) (2 pgs)
1		Hydrotech Flex-Flash Typical Flashing Details (4 pgs)

THESE ARE TRANSMITTED as checked below:

- ☒ For approval
- ☐ For your use
- ☐ As requested
- ☐ For review and comment
- ☐ FOR BIDS DUE



REMARKS:

PAVER SAMPLES AND COLORS ARE ONSITE.....Let me know if you should need anything else.

Copy: File

Signed: Thomas J Belgeri / Dept Mgr - StL 01