



GENERAL DESCRIPTION

Hydrotech's Monolithic Membrane 6125 is a highly modified rubberized asphalt.

rubberized membrane

BASIC USE

Hydrotech's Monolithic Membrane 6125 is specifically designed to be used as a roofing and/or waterproofing membrane typically on concrete substrates in vertical or horizontal applications such as roof decks, parking decks, reflecting pools, plazas, mechanical room sub-floors, foundation walls, tunnels and planters.

SIZES

Hydrotech's Monolithic Membrane 6125 is available in recyclable cardboard cartons containing individual 40 pound cakes of material.

TECHNICAL SPECIFICATIONS

PROPERTY	TEST METHOD	RESULT
FLASH POINT	ASTM D-92 CGSB-37.50-M89	502°F (261°C)
PENETRATION	ASTM D-5329 CGSB-37.50-M89	98 mm @77°F (25°C) 187mm @122°F (50°C)
FLOW	ASTM D-5329 CGSB-37.50-M89	1.0 mm @140°F (60°C)
TOUGHNESS	CGSB-37.50-M89	16.0 Joules
RATIO OF TOUGHNESS TO PEAK LOAD	CGSB-37.50-M89	0.069
WATER VAPOR PERMEABILITY	ASTM E-96, Procedure E CGSB-37.50-M89	0.3 ng/Pa(s)m ²
WATER ABSORPTION	CGSB-37.50-M89	0.11 gram weight gain
LOW TEMPERATURE FLEXIBILITY (-25°C)	CGSB-37.50-M89	No delamination, adhesion loss or cracking
LOW TEMPERATURE CRACK BRIDGING (-25°C)	CGSB-37.50-M89	No cracking, adhesion loss or splitting
HEAT STABILITY	CGSB-37.50-M89	No change in viscosity, penetration, flow or low temperature flexibility
VISCOSITY	CGSB-37.50-M89	11.0 seconds
WATER RESISTANCE (5 days @ 50°C)	CGSB-37.50-M89	No delamination, blistering, emulsification or deterioration

CONTINUED PAGE 2

PROPERTY	TEST METHOD	RESULT
SOFTENING POINT	ASTM D-36	180°F (82°C)
ELONGATION	ASTM D-5329	1000% minimum
RESILIENCY	ASTM D-5329	40% minimum
BOND TO CONCRETE	ASTM D-5329	Pass @0°F (-18°C)
ACID RESISTANCE	ASTM D-896, Procedure 7.1 (N-8)	Pass - 50% Nitric Acid - 50% Sulfuric Acid
RESISTANCE TO HYDROSTATIC PRESSURE	ASTM D-08.22, Draft 2 (developed: D5385)	100 psi (= 231 foot head of water)
RESISTANCE TO SALT WATER (20% sodium carbonate and calcium chloride)	ASTM D-896 similar	No delamination, blistering, emulsification or deterioration
RESISTANCE TO FERTILIZER (undiluted 15/5/5 nitrogen/phosphorus/potash)	ASTM D-896 similar	No delamination, blistering, emulsification or deterioration
RESISTANCE TO ANIMAL WASTE	3 year exposure	No deterioration
SOLIDS CONTENT		100%
SHELF LIFE		10 years (sealed)
SPECIFIC GRAVITY		1.15 ± 0.02

SUBMITTAL IDENTIFICATION SHEET

To be completed by Contractor/CM

PROJECT NAME	
ADDRESS	
NUMBER	
OWNER	
ARCHITECT / ENGINEER	
SUBMITTED BY	
CONTRACTOR / CM SUBMITTAL NO.	CANNON DESIGN SUBMITTAL NO.
DRAWING / DETAIL REFERENCE	SPECIFICATION SECTION / PARAGRAPH
MANUFACTURER / SUPPLIER	ITEM / PRODUCT ID
REQUIRED DATE	PRIORITY
CRITICALITY	

To be completed by Reviewer

CANNON DESIGN SUBMITTAL NUMBER
RECEIVED DATE

- ☐ **A. No Exceptions Taken**
No further review of submittal is required.
- ☐ **B. Make Corrections Noted**
Incorporate corrections in work;
resubmission is not required.
- ☐ **C. Revise and Resubmit**
Revise as noted, and resubmit for review.
- ☐ **D. Rejected**
Submittal is not in compliance with Contract Documents;
provide new submittal.
- ☐ **E. For Record / Information Only**
Submittal was reviewed for Record / Information
purposes only.
- ☐ **F. Not Required for Review**
Submittal is not required by Contract Documents
and has not been reviewed.

Review is for conformance with the design concept of this project and for general compliance with contract documents. Contractor is responsible for quantities, dimensions and compliance with contract documents and for information that pertains to fabrication processes, construction techniques and coordination of this work with all trades which will be affected thereby. This review is null and void if submittal deviates from contract documents and does not indicate or note deviations.

ITEM BEING SUBMITTED (check only one)

- ☐ Shop Drawings ☐ Certification / Qualifications ☐ Coordination Drawing
☐ Samples ☐ Record Documents ☐ Calculations
 (_____ copies) ☐ Product Data ☐ Schedules
☐ LEED Submittal ☐ O&M Manuals
☐ Other _____

ITEM BEING SUBMITTED FOR (check only one)

- ☐ Action ☐ Information Only ☐ Record

REMARKS OR DEVIATIONS

CONTRACTOR / CM CERTIFICATION
(SUBMITTALS NOT CERTIFIED WILL BE RETURNED WITHOUT REVIEW)



PARIC CORPORATION
SUBMITTAL STAMP

THIS SHOP DRAWING HAS BEEN REVIEWED BY PARIC CORPORATION

Subcontractor remains responsible for dimensions, quantities, coordination with other trades and compliance with contract documents.

Ry:

Devin D. Gates

REVIEWED BY	DATE

A/E COMMENTS

- ☐
- See attached sheet(s) for additional comments

REVIEWED BY	DATE



77 Westport Plaza
Suite 250
St. Louis, MO 63146

TRANSMITTAL

No. 15051-0347

Paric Corporation

PROJECT: 15051-Webster University Interdisciplinary Science Building

DATE: 11/29/2016

TO: Cannon Design
1100 Clark Ave
St Louis MO 63102

Fax;
314-241-2203

RE: Hot Fluid Applied Waterproofing at Pavers
Product Data

ATTN: Kelvin Patel

JOB: 15051

WE ARE SENDING:		SUBMITTED FOR:	ACTION TAKEN:
☐ Shop Drawings		☒ Approval	☐ Approved as Submitted
☐ Letter		☐ Your Use	☐ Approved as Noted
☐ Prints		☐ As Requested	☐ Returned After Loan
☐ Change Order		☐ Review and Comment	☐ Resubmit
☐ Plans			☐ Submit
☐ Samples		SENT VIA:	☐ Returned
☐ Specifications		☐ Attached	☐ Returned for Corrections
☒ Other: Product Data		☐ Separate Cover Via:	☐ Due Date:

Item	Package	Code	Rev.	Copies	Date	Description	Status
Submittal		071413-007	1		11/29/2016	Hot Fluid Applied Waterproofing at Pavers Product Data	Submitted

NOTES:

CC:

Signed: _____
Devin Gates