# JM EPDM LAP CAULK

## Features and Components

**Use:** To seal the edges around flashing terminations, peel and stick products and exposed edges of JM EPDM membrane cement splices.

**Type:** One-part, elastomeric sealant.

**Color:** Black

**Component**
SE Sealant

**Type**
M Membrane
FL Flashing

Single Ply

## System Compatibility

*This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.*

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Multi-Ply | BUR | | APP | | SBS | | | | |
| | HA | CA | CA | HW | HA | CA | HW | SA | |
| | ***Do not use in Multi-Ply systems*** | | | | | | | | |

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Single Ply | TPO | | PVC | | EPDM | | |
| | MF | FA | MF | FA | MF | FA | BA |
| | ***Used to seal Membrane laps in EPDM Single Ply systems*** | | | | | | |

**Key:** **HA** = Hot Applied **CA** = Cold Applied **HW** = Heat Weldable **SA** = Self Adhered **MF** = Mechanically Fastened **FA** = Fully Adhered **BA** = Ballasted

## Energy and the Environment

| | |
|---|---|
| Maximum VOC | 381-391 g/l |

## Precautions

*Johns Manville EPDM Lap Caulk is a combustible material and should be shipped and stored away from open flames, heat or sources of ignition. Keep all pails tightly sealed while in storage. It should be used only in well-ventilated areas. It may cause eye, skin and respiratory irritation, and is harmful or fatal if swallowed. Avoid contact with skin. Use impervious clothing and rubber gloves to avoid prolonged or repeated contact with skin. Read the container label and follow all safety instructions.*

## Installation/Application

Bead

- Apply to clean, dry, smooth substrates between 40°F and 120°F (4°C and 48°C).
- Refer to the application instructions guidelines for proper utilization of this caulk.

## Packaging and Coverage

| | |
|---|---|
| Container Size | Box of 16 - 10.3 oz (304.6 ml) tubes |
| Shipping Weight *(approx.)* | 12.2 lb (5.53 kg)/box ? |
| Pallets per Truck | 22 |
| Coverage Rate* *(approx.)* | 20 lin ft (6.09 lin m) per tube |

* Coverage, open and dry time rates can vary dramatically depending on the particular substrate and environmental conditions. Coverage rates stated herein are approximate only. If FM Global® or UL® approval is required, consult specific RoofNav℠ or the UL Certifications Directory for specific application rates.

## Storage

| | |
|---|---|
| Shelf Life | 12 months from manufacture date |
| Storage Conditions | Clean, dry, indoor environment, out of direct sunlight, in an unopened container |
| Temperature Range | 60°F – 80°F (16°C – 27°C) Protect from freezing |

Refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.

# JM EPDM LAP CAULK

Version 1.3 | Revision Date 05/29/2015 | Print Date 05/29/2015

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : JM EPDM LAP CAULK

Manufacturer or supplier's details

Company : Johns Manville
Address : P.O. Box 5108
Denver, CO USA 80127
Telephone : 303-978-2000 8:00AM-5:00PM M-F
Emergency telephone number : 1-800-424-9300 (Chemtrec, in English)

Prepared by : productsafety@jm.com

## SECTION 2. HAZARDS IDENTIFICATION

**GHS Classification**

Flammable liquids : Category 2

Carcinogenicity : Category 2

Specific target organ toxicity - single exposure : Category 3

Skin sensitisation : Category 1

**GHS Label element**

Hazard pictograms :

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer if inhaled.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
P272 Contaminated work clothing should not be allowed out of the workplace.
**Response:**
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
**Storage:**
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
**Disposal:**
P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Hazardous components**

| Chemical Name | CAS-No. | Concentration (%) |
|---|---|---|
| Solvent naphtha (petroleum), light aliph. | 64742-89-8 | >= 20 - < 30 |
| Stoddard solvent | 8052-41-3 | >= 10 - < 20 |
| kaolin | 1332-58-7 | >= 5 - < 10 |
| Mineral Oil | Not Assigned | >= 5 - < 10 |

## SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.

| | | |
|---|---|---|
| In case of eye contact | : | Remove contact lenses.<br>Immediately flush eye(s) with plenty of water.<br>Protect unharmed eye.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist. |
| If swallowed | : | Keep respiratory tract clear.<br>Do NOT induce vomiting.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician.<br>Take victim immediately to hospital. |

## SECTION 5. FIREFIGHTING MEASURES

| | | |
|---|---|---|
| Suitable extinguishing media | : | Alcohol-resistant foam<br>Carbon dioxide (CO2)<br>Dry chemical |
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during firefighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | No hazardous combustion products are known |
| Specific extinguishing methods | : | Standard procedure for chemical fires. |
| Further information | : | Standard procedure for chemical fires.<br>Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.<br>For safety reasons in case of fire, cans should be stored separately in closed containments.<br>Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |

## SECTION 6. ACCIDENTAL RELEASE MEASURES

| | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.<br>Ensure adequate ventilation.<br>Remove all sources of ignition.<br>Evacuate personnel to safe areas.<br>Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions | : | Prevent product from entering drains.<br>Prevent further leakage or spillage if safe to do so.<br>If the product contaminates rivers and lakes or drains inform |

respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Components with workplace control parameters**

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---|---|---|---|---|
| Solvent naphtha (petroleum), light aliph. | 64742-89-8 | TWA | 500 ppm<br>2,000 mg/m3 | OSHA |
| | | TWA | 400 ppm<br>1,600 mg/m3 | OSHA |
| Stoddard solvent | 8052-41-3 | TWA | 100 ppm | ACGIH |
| | | TWA | 350 mg/m3 | NIOSH REL |
| | | C | 1,800 mg/m3 | NIOSH REL |
| | | TWA | 500 ppm<br>2,900 mg/m3 | OSHA |
| | | TWA | 100 ppm<br>525 mg/m3 | OSHA |
| kaolin | 1332-58-7 | TWA (Respirable fraction) | 2 mg/m3 | ACGIH |

| | | | | |
|---|---|---|---|---|
| | | TWA (Respirable) | 5 mg/m3 | NIOSH REL |
| | | TWA (total) | 10 mg/m3 | NIOSH REL |
| | | TWA (Total dust) | 10 mg/m3 | OSHA |
| | | TWA (respirable dust fraction) | 5 mg/m3 | OSHA |
| Mineral Oil | Not Assigned | (Mist) | 5 mg/m3 | NIOSH REL |
| | | STEL (Mist) | 10 mg/m3 | NIOSH REL |
| | | PEL (Mist) | 5 mg/m3 | OSHA |
| | | TWA (Inhalable fraction) | 5 mg/m3 | ACGIH |
| carbon black (extracts) | 1333-86-4 | TWA | 3.5 mg/m3 | NIOSH REL |
| | | TWA | 3.5 mg/m3 | OSHA |
| | | TWA | 3.5 mg/m3 | OSHA |
| | | TWA | 0.1 mg/m3 (PAHs) | NIOSH REL |
| | | TWA (Inhalable fraction) | 3 mg/m3 | ACGIH |
| titanium dioxide | 13463-67-7 | TWA (total dust) | 15 mg/m3 | OSHA |
| | | TWA (Total dust) | 10 mg/m3 | OSHA |
| | | TWA | 10 mg/m3 (Titanium dioxide) | ACGIH |

**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection
Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Eye protection : Tightly fitting safety goggles

Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
Written instructions for handling must be available at the work place.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|---|---|---|
| Appearance | : | paste |
| Colour | : | black |
| Odour | : | No data available |
| Odour Threshold | : | No data available |
| pH | : | No data available |
| Melting point/freezing point | : | No data available |
| Boiling point/boiling range | : | 85 ℃<br>(1,013.33 hPa) |
| Flash point | : | 10 ℃<br>estimated |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Upper explosion limit | : | 8 %(V) |
| Lower explosion limit | : | 1 %(V) |
| Vapour pressure | : | No data available |
| Relative vapour density | : | No data available |
| Relative density | : | No data available |
| Density | : | 0.988 g/cm3 (20 ℃) |
| Solubility(ies) | | |
| Water solubility | : | practically insoluble |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Auto-ignition temperature | : | No data available |
| Thermal decomposition | : | No data available |
| Viscosity | | |
| Viscosity, dynamic | : | ca. 600,000 mPa.s (20 ℃) |
| Viscosity, kinematic | : | > 7 mm2/s (40 ℃) |

## SECTION 10. STABILITY AND REACTIVITY

| | | |
|---|---|---|
| Reactivity | : | No decomposition if stored and applied as directed. |
| Chemical stability | : | No decomposition if stored and applied as directed. |
| Possibility of hazardous reactions | : | No decomposition if stored and applied as directed.<br>Vapours may form explosive mixture with air. |
| Conditions to avoid | : | Heat, flames and sparks. |

## SECTION 11. TOXICOLOGICAL INFORMATION

**Acute toxicity**

**Product:**

| | | |
|---|---|---|
| Acute oral toxicity | : | Acute toxicity estimate : > 5,000 mg/kg<br>Method: Calculation method |
| Acute inhalation toxicity | : | Acute toxicity estimate : 11333 ppm<br>Exposure time: 4 h<br>Test atmosphere: gas<br>Method: Calculation method |

**Acute toxicity**

**Components:**

**Solvent naphtha (petroleum), light aliph.:**

| | | |
|---|---|---|
| Acute oral toxicity | : | LD50 (Rat): > 8,000 mg/kg |
| Acute inhalation toxicity | : | LC50 (Rat): 3400 ppm<br>Exposure time: 4 h |
| Acute dermal toxicity | : | LD50 (Rat): > 4,000 mg/kg |

**Acute toxicity**

**kaolin:**

| | | |
|---|---|---|
| Acute oral toxicity | : | LD50 (Rat): > 5,000 mg/kg |
| Acute dermal toxicity | : | LD50 (Rat): > 5,000 mg/kg |

**Acute toxicity**

**Mineral Oil:**

| | | |
|---|---|---|
| Acute oral toxicity | : | LD50 Oral (Rat): 50,000 mg/kg |
| Acute dermal toxicity | : | LD50 Dermal (Rat): > 2,000 mg/kg |

**Germ cell mutagenicity**

**Components:**

**Solvent naphtha (petroleum), light aliph.:**

| | | |
|---|---|---|
| Germ cell mutagenicity- | : | In vivo tests showed mutagenic effects |

Assessment

**Carcinogenicity**

**Components:**

**Solvent naphtha (petroleum), light aliph.:**
Carcinogenicity - Assessment : Possible human carcinogen

| | | |
|---|---|---|
| **IARC** | Group 1: Carcinogenic to humans | |
| | kaolin | 1332-58-7 |
| | Group 2B: Possibly carcinogenic to humans | |
| | carbon black (extracts) | 1333-86-4 |
| | titanium dioxide | 13463-67-7 |
| **ACGIH** | Confirmed animal carcinogen with unknown relevance to humans | |
| | carbon black (extracts) | 1333-86-4 |
| **OSHA** | No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. | |
| **NTP** | Known to be human carcinogen | |
| | kaolin | 1332-58-7 |

**Aspiration toxicity**

**Components:**

**Solvent naphtha (petroleum), light aliph.:**
May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks: Solvents may degrease the skin.

## SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

| | | |
|---|---|---|
| Regulation | | 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances |
| Remarks | | This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). |
| Additional ecological information | : | No data available |

## SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

| | | |
|---|---|---|
| Disposal of residual product | : | Do not dispose of waste into sewer.<br>Do not contaminate ponds, waterways or ditches with chemical or used container.<br>Send to a licensed waste management company. |
| Contaminated packaging | : | Empty remaining contents.<br>Dispose of as unused product.<br>Do not re-use empty containers.<br>Do not burn, or use a cutting torch on, the empty drum. |

## SECTION 14. TRANSPORT INFORMATION

**International transport regulations**

US DOT: UN1133 Adhesive, 3, II Limited Quantity

## SECTION 15. REGULATORY INFORMATION

**TSCA list** : Not relevant

Not relevant

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|---|---|---|---|
| benzene | 71-43-2 | 10 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).
This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).
This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

**California Prop 65** WARNING! This product contains a chemical known to the State of California to cause cancer.

| | |
|---|---|
| carbon black (extracts) | 1333-86-4 |
| titanium dioxide | 13463-67-7 |
| Crystalline silica | 14808-60-7 |
| ethylbenzene | 100-41-4 |
| benzene | 71-43-2 |
| naphthalene | 91-20-3 |

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

| | |
|---|---|
| benzene | 71-43-2 |
| toluene | 108-88-3 |

**The components of this product are reported in the following inventories:**

TSCA : Listed on TSCA

: Mineral Oil

: POLYMER

DSL : All components of this product are on the Canadian DSL.

: Mineral Oil

: POLYMER

## SECTION 16. OTHER INFORMATION

**Further information**

Revision Date : 05/29/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CANNONDESIGN

# SUBMITTAL IDENTIFICATION SHEET

**To be completed by Contractor/CM**

WEBSTER UNIVERSITY ISB
PROJECT NAME

8274 BIG BEND BLVD
ADDRESS

NUMBER

WEBSTER UNIVERSITY
OWNER

CANNON DESIGN
ARCHITECT / ENGINEER

DEVIN D GATES
SUBMITTED BY

075323-001
CONTRACTOR / CM SUBMITTAL NO.

CANNON DESIGN SUBMITTAL NO.

DRAWING / DETAIL REFERENCE

075323
SPECIFICATION SECTION / PARAGRAPH

MANUFACTURER / SUPPLIER

ITEM / PRODUCT ID

REQUIRED DATE

PRIORITY

CRITICAL

ITEM BEING SUBMITTED (check only one)

- ○ Shop Drawings
- ○ Samples ( _____ copies)
- ○ LEED Submittal
- ○ Certification / Qualifications
- ○ Record Documents
- ○ Product Data
- ○ Coordination Drawing
- ○ Calculations
- ○ Schedules
- ○ O&M Manuals
- ○ Other _____

ITEM BEING SUBMITTED FOR (check only one)

○ Action ○ Information Only ○ Record

REMARKS OR DEVIATIONS

Email correspondence with KWA provided clarifications for requested information and warranty letter attached.

CONTRACTOR / CM CERTIFICATION
(SUBMITTALS NOT CERTIFIED WILL BE RETURNED WITHOUT REVIEW)

PARIC

PARIC CORPORATION
SUBMITTAL STAMP

THIS SHOP DRAWING HAS BEEN REVIEWED BY PARIC CORPORATION

Subcontractor remains responsible for dimensions, quantities, coordination with other trades and compliance with contract documents.

By:
Devin D. Gates

DEVIN D GATES — 10/11/16
REVIEWED BY — DATE

**To be completed by Reviewer**

07 5323-001 REV002
CANNON DESIGN SUBMITTAL NUMBER

10/11/16
RECEIVED DATE

- ○ A. No Exceptions Taken
  No further review of submittal is required.
- ● B. Make Corrections Noted
  Incorporate corrections in work; resubmission is not required.
- ○ C. Revise and Resubmit
  Revise as noted, and resubmit for review.
- ○ D. Rejected
  Submittal is not in compliance with Contract Documents; provide new submittal.
- ○ E. For Record / Information Only
  Submittal was reviewed for Record / Information purposes only.
- ○ F. Not Required for Review
  Submittal is not required by Contract Documents and has not been reviewed.

Review is for conformance with the design concept of this project and for general compliance with contract documents. Contractor is responsible for quantities, dimensions and compliance with contract documents and for information that pertains to fabrication processes, construction techniques and coordination of this work with all trades which will be af
This review is null and void if submittal deviates from contra
and does not indicate or note deviations.

A/E COMMENTS ○ See attached sheet(s) for additional comments

Final warranty must meet specification section 1.10. 2. requirements: wind speed coverage of that indicated on structural drawings (90 mph minimum), hail coverage for up to 2 inch diameter, and accidental puncture coverage of 16 man hours per year of warranty.

see comments below

Kathy Williams — 10/11/16
REVIEWED BY — DATE

## Gates, Devin

**From:** Scott Klingsick <scott@kwastl.com>
**Sent:** Friday, October 07, 2016 7:00 AM
**To:** Gates, Devin
**Cc:** kpatel@cannondesign.com
**Subject:** RE: Clarifications on returned EPDM shop drawings

**Follow Up Flag:** Follow up
**Flag Status:** Flagged

Yes this will be acceptable. We need the rest of the information revised and it to be resubmitted so we can approve submittal 075323-001. Thanks

**Scott Klingsick,** LEED Green Associate
Project Manager
9721 Litzsinger Rd.
St. Louis, MO 63124
(p) 314.962.2560 (f) 314.962.4057
scott@kwastl.com

KWA architecture / landscape architecture / interiors
KWA Architects

You have requested Kathy Williams and Associates, LLC dba KWA to supply electronic media containing plans for use by your company. Due to the potential that the information set forth on the electronic media can be modified, unintentionally or otherwise, the use of such electronic media will be at your company's sole risk and without any liability, risk or exposure to KWA LLC (Kathy Williams & Associates). You will not be automatically updated on revisions and/or modifications to the attached. **CONFIDENTIAL** The information, data and drawings embodied in this document are strictly confidential and are supplied with the understanding that they will not be disclosed to third parties without the prior written consent of the Owner.

---

**From:** Gates, Devin [mailto:ddgates@paric.com]
**Sent:** Thursday, October 06, 2016 4:59 PM
**To:** Scott Klingsick
**Cc:** kpatel@cannondesign.com
**Subject:** RE: Clarifications on returned EPDM shop drawings

Kelvin/Scott,

Were you able to take a look at this and does this resolve the impact resistance needs? I can resubmit formally as needed but with the back and forth I wanted to ensure we are all on the same page.

Thanks,

DEVIN GATES
SENIOR PROJECT ENGINEER

**Cell:** 314-348-8828
**Main:** 636-561-9500

- - - - - -
77 Westport Plaza, Suite 250
St. Louis, MO 63146

**PARIC.COM**

Please consider your environmental responsibility before printing this e-mail

This e-mail message and any files transmitted with it may be CONFIDENTIAL and are intended for the addressee only. Any unauthorized use, dissemination of the information, or copying of this message is prohibited. If you are not the intended addressee, please notify the sender immediately and delete this message.

---

**From:** Aaron Hammerstone [mailto:aaron.hammerstone@kirberg.com]
**Sent:** Tuesday, October 04, 2016 7:10 AM
**To:** Gates, Devin; scott@kwastl.com
**Cc:** kpatel@cannondesign.com
**Subject:** FW: Clarifications on returned EPDM shop drawings

All,

Please see the two attachments, as well as the information in the below email in regards to the ASTM testing on JM EPDM membrane.

Thanks

---

**Aaron Hammerstone | Project Manager**

314.333.4710 Direct | aaron.hammerstone@kirberg.com

314.792.3777 Mobile

**KIRBERG COMPANY**
State-of-the Art Roofing and More. Since 1920.

1400 South Third Street Saint Louis, MO 63104
314.534.4444 Main | 314.534.2626 Fax

866.KIRBERG Toll-Free | http://www.kirberg.com/

Nationwide Service.
Founding Member of RoofConnect.
http://www.roofconnect.com/

********** NOTICE **********
The information contained in this e-mail, and in any accompanying documents, may constitute confidential and/or legally privileged information. The information is intended only for use by the designated recipient. If you are not the intended recipient (or responsible for the delivery of the message to the intended recipient), you are hereby notified that any dissemination, distribution, copying, or other use of, or taking of any action in reliance on this e-mail is strictly prohibited. If you have received this e-mail communication in error, please notify the sender immediately and delete the message from your system. All e-mail sent to and from this address will be received or otherwise recorded by the Kirberg Roofing, Inc e-mail system and is subject to archival, monitoring or review by, and/or disclosure to, someone other than the recipient.

---

**From:** Mark Tucker [mailto:Mark@D7Reps.com]
**Sent:** Monday, October 03, 2016 4:12 PM
**To:** Aaron Hammerstone

**Cc:** James Nunns; zac.stallings@jm.com; Jim Schriefer
**Subject:** RE: Clarifications on returned EPDM shop drawings

Aaron,

This JM EPDM 90NR data sheet shows we meet ASTM 4637 for EPDM. It's the same testing All EPDM is to meet, requiring minimum test results for numerous categories. There are three major manufacturers of EPDM: Johns Manville, Firestone, and Carlisle. NOTE: of the three, the latter two, have private label products, targeting a different market segment of contractors. The 3 major manufacturers are also, the only three members of the EPDM Roofing Association (ERA): http://www.epdmroofs.org/about-era/members . The goal of this organization is collectively establish current and accurate data documenting of EPDM. http://www.epdmroofs.org/about-era/who-we-are .

Inside of **ASTM D 4637**, are individual tests for certain criteria. As a whole, make up ASTM D 4637.
Of which include the following:
**ASTM D 5635 – Dynamic Puncture Resistance, 5J, Type 1 – Passes**
**ASTM D 5602 Static Puncture Resistance, 44.1 lbf, Type 1 – Passes**

There are only two hail tests for the Single Ply Membranes (according to Jim D. Koontz- Crenshaw and Koontz). Of which, the one most recognized, is FM's test, for approved Roof Nav assemblies per FM 4470.
For this project, we supplied the following two FM Nav #'s:

Assembly Properties

| | | | |
|---|---|---|---|
| Assembly #: | **392147-0-0** | Slope: | 1.0000 |
| Roof System: | Single-Ply System | Wind Uplift*: | 90 |
| Application: | New Roof | Internal Fire: | 1 |
| Cover Securement: | Adhered | Exterior Fire: | A |
| Deck Type: | Steel | Hail: | SH |
| | For Use With Non-Combustible Walls: | | No |

AND

| | | | |
|---|---|---|---|
| Assembly #: | **374588-0-0** | Slope: | 1.0000 |
| Roof System: | Single-Ply System | Wind Uplift*: | 270 |
| Application: | New Roof | Internal Fire: | NC |
| Cover Securement: | Adhered | Exterior Fire: | A |
| Deck Type: | Structural Concrete | Hail: | SH |
| | For Use With Non-Combustible Walls: | | No |

The roofing specification for this project, states in Part 1, paragraph 1.5, line 3, That the manufacturer must meet "Tested and listed by FM for class specified in "Performance Requirements" Article in Part 2 of this Section". In Part 2, **we met** Part 2, paragraph 2.2, A1. As noted, A2 criteria is for Modified Roofing. As such, A2 should be eliminated from requirements of the submittal, as **Part 2, 2.2, D.2** requires a Hail Resistance: SH. Of which, is met with both of the approved JOHNS MANVILLE Roof Nav Assembly numbers provided.

As for UL 2818, again is not a test used in the Single Ply industry. It is used primarily in the residential steep slope roofing market (shingles, tile, slate, metal roofs). The test requirementfor this, is to test roof slopes at 6" in 12" or greater. This test was a realized in 1996, by Major Property Insurers, the Institute of

Business and Home Safety (IBHS), and with United Laboratory. They developed ASMT 2218, to set a national standard, for roof impact resistance, for the residential steep slope market.

- 
- A scope/ description, for the use of ASTM 2218, from the UL ASTM 2218 web page: http://www.comm-2000.com/ProductDetail.aspx?UniqueKey=20884 click on “scope”.
- 1 Scope

  1.1 This test method provides impact resistance data for the evaluation of prepared roof covering materials. For purposes of this Standard prepared roof covering materials are considered to be small units, sheets or panels designed for installation with multiple layers of such materials installed in **overlapping rows normally on inclines exceeding 25 percent**.

We did a quick research of other manufacturers web sites, and on hand manufacturers data. Not one in the Single Ply manufacturing business, list or utilize the UL 2218 test. In fact, all manufacturers use the same testing, as it relates to the ASTM (see above for Static and Dynamic Puncturing) for that membrane. In this project instance, is EPDM (ASTM D 4637).

It appears to us, that there seems to be a mix of an EPDM specification, and a Modified/ Residential specification.

If this information does not satisfy the needs of the BID Documents, please let me know.

Mark

---

**From:** Aaron Hammerstone [mailto:aaron.hammerstone@kirberg.com]
**Sent:** Friday, September 30, 2016 2:25 PM
**To:** Mark Tucker <Mark@D7Reps.com>
**Subject:** Fwd: Clarifications on returned EPDM shop drawings

Thanks,

Aaron Hammerstone

Project Manager
Kirberg Company
(314)792-3777

Begin forwarded message:

> **From:** Scott Klingsick <scott@kwastl.com>
> **Date:** September 30, 2016 at 2:24:29 PM CDT
> **To:** Aaron Hammerstone <aaron.hammerstone@kirberg.com>, "Gates, Devin" <ddgates@paric.com>
> **Cc:** "Szachnieski, Jason" <JRSzachnieski@paric.com>, Kathy Williams <kathy@kwastl.com>
> **Subject: RE: Clarifications on returned EPDM shop drawings**
>
> Aaron,

Sorry for the confusion. The wrong ASTM number listed in the specification. It should have been ASTM D 4637-08 “Specification for EPDM Sheet Used in Single-ply Roof Membrane” and/or UL 2218 Standard for Impact Resistance of Prepared Roof Covering Materials. We need testing and product data to show compliance with the requirements impact resistance for the hail requirements on this project.

**Scott Klingsick,** LEED Green Associate
Project Manager
9721 Litzsinger Rd.
St. Louis, MO 63124
(p) 314.962.2560 (f) 314.962.4057
scott@kwastl.com

KWA Architects

You have requested Kathy Williams and Associates, LLC dba KWA to supply electronic media containing plans for use by your company. Due to the potential that the information set forth on the electronic media can be modified, unintentionally or otherwise, the use of such electronic media will be at your company's sole risk and without any liability, risk or exposure to KWA LLC (Kathy Williams & Associates). You will not be automatically updated on revisions and/or modifications to the attached. **CONFIDENTIAL** The information, data and drawings embodied in this document are strictly confidential and are supplied with the understanding that they will not be disclosed to third parties without the prior written consent of the Owner.

---

**From:** Aaron Hammerstone [mailto:aaron.hammerstone@kirberg.com]
**Sent:** Friday, September 30, 2016 12:13 PM
**To:** Gates, Devin; Scott Klingsick
**Cc:** Szachnieski, Jason
**Subject:** Re: Clarifications on returned EPDM shop drawings

ASTM D 3746 is for bituminous roofing. ASTM D 4272 is for plastic films.

This is an EPDM roof system. I think I'm missing something here.

Thanks,

Aaron Hammerstone

Project Manager
Kirberg Company
(314)792-3777

On Sep 30, 2016, at 11:26 AM, Gates, Devin <ddgates@paric.com> wrote:

> Aaron,
>
> See convo below regarding the shop drawing markups.
>
> DEVIN GATES
> SENIOR PROJECT ENGINEER
>
> **Direct:** 636-561-9592
> **Main:** 636-561-9500

**Cell:** 314-348-8828
- - - - - -
77 Westport Plaza, Suite 250
St. Louis, MO 63146

Sent from my iPhone

Begin forwarded message:

> **From:** "Patel, Kelvin" <kpatel@CANNONDESIGN.COM>
> **Date:** September 30, 2016 at 11:21:32 AM CDT
> **To:** "Gates, Devin" <ddgates@paric.com>, "Szachnieski, Jason" <JRSzachnieski@paric.com>
> **Cc:** "Grossman, Lynn" <lgrossman@CANNONDESIGN.COM>
> **Subject: FW: Clarifications on returned EPDM shop drawings**
>
> Devin,
>
> See clarification from KWA below.
>
> Thanks,
>
> Kelvin Patel, CDT, LEED AP BD+C
> Associate
> T 314.425.8756
>
> ---
>
> **From:** Scott Klingsick [mailto:scott@kwastl.com]
> **Sent:** Friday, September 30, 2016 11:13 AM
> **To:** Patel, Kelvin <kpatel@CANNONDESIGN.COM>; Kathy Williams <kathy@kwastl.com>
> **Cc:** Grossman, Lynn <lgrossman@CANNONDESIGN.COM>
> **Subject:** RE: Clarifications on returned EPDM shop drawings
>
> Kelvin,
>
> It is fine to show the building taller than 60' information. We do need submittal for the 2.2 A.2. Impact Resistance: Test reports and product data showing compliance with ASTM D 3746 or ASTM D 4272. Thanks
>
> **Scott Klingsick,** LEED Green Associate
> Project Manager
> 9721 Litzsinger Rd.
> St. Louis, MO 63124
> (p) 314.962.2560 (f) 314.962.4057
> scott@kwastl.com

You have requested Kathy Williams and Associates, LLC dba KWA to supply electronic media containing plans for use by your company. Due to the potential that the information set forth on the electronic media can be modified, unintentionally or otherwise, the use of such electronic media will be at your company's sole risk and without any liability, risk or exposure to KWA LLC (Kathy Williams & Associates). You will not be automatically updated on revisions and/or modifications to the attached. **CONFIDENTIAL** The information, data and drawings embodied in this document are strictly confidential and are supplied with the understanding that they will not be disclosed to third parties without the prior written consent of the Owner.

---

**From:** Patel, Kelvin [mailto:kpatel@CANNONDESIGN.COM]
**Sent:** Thursday, September 29, 2016 1:14 PM
**To:** Scott Klingsick; Kathy Williams
**Cc:** Grossman, Lynn
**Subject:** FW: Clarifications on returned EPDM shop drawings

Kathy / Scott,

Please review Paric's questions and provide comments.

Thanks,

Kelvin Patel, CDT, LEED AP BD+C
Associate
T 314.425.8756

---

**From:** Gates, Devin [mailto:ddgates@paric.com]
**Sent:** Thursday, September 29, 2016 1:04 PM
**To:** Patel, Kelvin <kpatel@CANNONDESIGN.COM>
**Cc:** Szachnieski, Jason <JRSzachnieski@paric.com>
**Subject:** Clarifications on returned EPDM shop drawings

Kelvin,

I have a couple of clarifications on two items from the attached rejected submittal.

1. On page 3 the perimeter and corner dimensions are crossed out for buildings taller than 60' however this building is higher than 60' in locations, is this note correct?
2. Can you please be more specific on what is being requested in the note "submit information for A2"? Johns Mansville did not feel like any of this section applies to the EPDM roof.

Thank you,

DEVIN GATES
SENIOR PROJECT ENGINEER

**Cell:** 314-348-8828
**Main:** 636-561-9500

- - - - - -

77 Westport Plaza, Suite 250
St. Louis, MO 63146

PARIC.COM

Please consider your environmental responsibility before printing this e-mail

This e-mail message and any files transmitted with it may be CONFIDENTIAL and are intended for the addressee only. Any unauthorized use, dissemination of the information, or copying of this message is prohibited. If you are not the intended addressee, please notify the sender immediately and delete this message.

<image005.png>

<image004.png>

<image005.png>

<image006.png>

<image007.jpg>