

Features and Components

Use: JM EPDM/PVC Pourable Sealer is used as a penetration pocket filler.

Type: Two-part polyurethane sealant.

Colors: Part A: Black
Part B: Amber



Component
SE
Sealant

Type
FP
Penetration
Single Ply

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
Do not use in Multi-Ply systems									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
Used to fill Penetration Pockets in the selected Single Ply systems above							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Energy and the Environment

Maximum VOC	Part A & B: 0 g/l
-------------	-------------------

Physical Properties

Property		JM EPDM/PVC Pourable Sealer
Percent Volatile	Part A	0%
	Part B	0%
Specific Gravity @ 77°F (25°C)	Part A	1.51
	Part B	1.24
Vapor Pressure	Part A	< 0.001 @ 68°F (20°C)
	Part B	< 1x10 ⁻⁵ mm Hg @ 77°F (25°C)

Precautions

Johns Manville EPDM/PVC Pourable Sealer is a combustible material and should be shipped and stored away from open flames, heat or sources of ignition. Keep all cans tightly sealed while in storage. It should be used only in well-ventilated areas. It may cause eye, skin and respiratory irritation, and is harmful or fatal if swallowed. Avoid contact with skin. Use impervious clothing and rubber gloves to avoid prolonged or repeated contact with skin. Read the container label and follow all safety instructions.

Installation/Application



- Apply between temperatures of: 40° to 90° Do Not Thin.
- Refer to the application instructions guidelines for proper utilization of this sealant.

Packaging and Coverage

Container Sizes	Box of three kits: Part A: 0.75 gal (2.84 l) can Part B: 0.5 pint (0.24 l) can
Weight per Can	Part A: 8.7 lb (3.95 kg) Part B: 0.57 lb (0.26 kg)
Shipping Weight (approx.)	32 lb (14.5 kg)/box
Boxes per Pallet	45
Pallet Weight (approx.)	1,500 lb (681.8 kg)
Pallets per Truck	8 (depends on order size)

Storage

Shelf Life	12 months from manufacture date
Storage Conditions	Clean, dry, indoor environment in an unopened container
Temperature Range	60°F – 75°F (16°C – 24°C) - Protect from freezing

Exposure Window

Workable pot life after mixing is approximately 30 minutes at 72°F (22°C). The material begins to cure firmly 2 hours after mixing.

JM EPDM/PVC Pourable Sealer - Part A

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : JM EPDM Pourable Sealer-Part A, JM PVC Pourable Sealer
- Part A

Manufacturer or supplier's details

Company : Johns Manville
Address : P.O. Box 5108
Denver, CO USA 80127
Telephone : 303-978-2000 8:00AM-5:00PM M-F
Emergency telephone : 1-800-424-9300 (Chemtrec, in English)
number

Prepared by : productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Not a hazardous substance or mixture.

GHS Label element

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous components**

Non-hazardous according to 29 CFR 1910.1200, when used as intended.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical
advice.
If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.
Immediately flush eye(s) with plenty of water.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

JM EPDM/PVC Pourable Sealer - Part A

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

- | | | |
|---|---|--|
| Unsuitable extinguishing media | : | High volume water jet |
| Hazardous combustion products | : | No hazardous combustion products are known |
| Specific extinguishing methods | : | Standard procedure for chemical fires. |
| Further information | : | Standard procedure for chemical fires. |
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment. |
| Environmental precautions | : | Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : | Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal. |

SECTION 7. HANDLING AND STORAGE

- | | | |
|-----------------------------|---|--|
| Advice on safe handling | : | Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations. |
| Conditions for safe storage | : | Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards. |

JM EPDM/PVC Pourable Sealer - Part A

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters****Personal protective equipment**

Respiratory protection	: In the case of vapour formation use a respirator with an approved filter.
Hand protection	
Remarks	: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
Eye protection	: Tightly fitting safety goggles
Skin and body protection	: impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. Written instructions for handling must be available at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: black
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available

JM EPDM/PVC Pourable Sealer - Part A

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: 1.5
Density	: 12.6 lb/gal
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available

SECTION 11. TOXICOLOGICAL INFORMATION**Further information****Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

JM EPDM/PVC Pourable Sealer - Part A

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Disposal of residual product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International transport regulations**

These products are not classified as dangerous goods according to international transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : Not relevant
Not relevant

EPCRA - Emergency Planning and Community Right-to-Know Act**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

JM EPDM/PVC Pourable Sealer - Part A

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

This material does not contain any components with a section 304 EHS RQ.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

Crystalline silica

14808-60-7

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

SECTION 16. OTHER INFORMATION**Further information**

Revision Date : 05/29/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

JM EPDM/PVC Pourable Sealer-Part B

Version 1.2

Revision Date 01/27/2016

Print Date 01/27/2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : JM EPDM/PVC Pourable Sealer-Part B

Manufacturer or supplier's details

Company : Johns Manville
Address : P.O. Box 5108
Denver, CO USA 80127
Telephone : +1 303-978-2000 8:00AM-5:00PM M-F
Emergency telephone : 1-800-424-9300 (Chemtrec, in English)
number

Prepared by : productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Inhalation) : Category 4
Skin irritation : Category 2
Eye irritation : Category 2B
Respiratory sensitisation : Category 1
Skin sensitisation : Category 1
Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure
Specific target organ toxicity : Category 1 (Respiratory Tract)
- repeated exposure

GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : H320 Causes eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H372 Causes damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.

Precautionary statements : **Prevention:**

JM EPDM/PVC Pourable Sealer-Part B

Version 1.2

Revision Date 01/27/2016

Print Date 01/27/2016

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear eye protection/ face protection.
P280 Wear protective gloves.
P285 In case of inadequate ventilation wear respiratory protection.
P270 Do not eat, drink or smoke when using this product.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 Store in a well-ventilated place.
P404 Store in a closed container.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
Diphenylmethanediisocyanate	9016-87-9	>= 30 - < 50
4,4'-methylenediphenyl diisocyanate	101-68-8	>= 20 - < 30

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Call a physician or poison control centre immediately.
If unconscious place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

JM EPDM/PVC Pourable Sealer-Part B

Version 1.2

Revision Date 01/27/2016

Print Date 01/27/2016

- | | |
|---|--|
| In case of eye contact | : Remove contact lenses.
Immediately flush eye(s) with plenty of water.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |
| Most important symptoms and effects, both acute and delayed | : None known. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|--|
| Unsuitable extinguishing media | : High volume water jet |
| Hazardous combustion products | : Hazardous decomposition products due to incomplete combustion |
| Specific extinguishing methods | : Standard procedure for chemical fires. |
| Further information | : Standard procedure for chemical fires. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.
Ensure adequate ventilation. |
| Environmental precautions | : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal. |

SECTION 7. HANDLING AND STORAGE

- | | |
|---|---|
| Advice on protection against fire and explosion | : Normal measures for preventive fire protection. |
|---|---|

JM EPDM/PVC Pourable Sealer-Part B

Version 1.2

Revision Date 01/27/2016

Print Date 01/27/2016

- Advice on safe handling : Avoid formation of aerosol.
 Do not breathe vapours/dust.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Dispose of rinse water in accordance with local and national regulations.
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.
 Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.05 mg/m3	NIOSH REL
		C	0.02 ppm 0.2 mg/m3	NIOSH REL
		C	0.02 ppm 0.2 mg/m3	OSHA
		C	0.02 ppm 0.2 mg/m3	OSHA

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

- Eye protection : Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing

JM EPDM/PVC Pourable Sealer-Part B

Version 1.2

Revision Date 01/27/2016

Print Date 01/27/2016

problems.

- Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
Written instructions for handling must be available at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Colour : No data available
- Odour : slight
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : 406 °F
- Flash point : No data available
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : 5 mmHg
- Relative vapour density : 8.5
- Relative density : No data available
- Density : 9.01 lb/gal
- Solubility(ies)
Water solubility : insoluble
- Solubility in other solvents : No data available
- Partition coefficient: n-octanol/water : No data available

JM EPDM/PVC Pourable Sealer-Part B

Version 1.2

Revision Date 01/27/2016

Print Date 01/27/2016

Auto-ignition temperature : No data available

Thermal decomposition : No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : If contained in exposed to high heat, 400°F it can be pressurized and possibility rupture. MDI reacts slowly with water to form CO₂ gas. This gas can cause sealed container to expand and possibly rupture.

Incompatible materials : Strong bases
Amines

Hazardous decomposition products : Hazardous decomposition products due to incomplete combustion
Nitrogen oxides (NO_x)

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute inhalation toxicity : Acute toxicity estimate : 15.71 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

JM EPDM/PVC Pourable Sealer-Part B

Version 1.2

Revision Date 01/27/2016

Print Date 01/27/2016

Respiratory or skin sensitisation**Product:**

Remarks: May cause sensitisation of susceptible persons by skin contact or by inhalation of aerosol or dust.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological information : No data available

JM EPDM/PVC Pourable Sealer-Part B

Version 1.2

Revision Date 01/27/2016

Print Date 01/27/2016

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Disposal of residual product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International transport regulations**

These products are not classified as dangerous goods according to international transport regulations.

SECTION 15. REGULATORY INFORMATION**TSCA list**

TSCA - 5(a) Significant New Use Rule List of Chemicals : Not relevant

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D) : Not relevant

EPCRA - Emergency Planning and Community Right-to-Know Act**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
4,4'-methylenediphenyl diisocyanate	101-68-8	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Diphenylmethanediisocyanate 9016-87-9 30 %

JM EPDM/PVC Pourable Sealer-Part B

Version 1.2

Revision Date 01/27/2016

Print Date 01/27/2016

4,4'-methylenediphenyl diisocyanate	101-68-8	20 %
--	----------	------

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

4,4'-methylenediphenyl diisocyanate	101-68-8	20 %
--	----------	------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

4,4'-methylenediphenyl diisocyanate	101-68-8	20 %
--	----------	------

California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

SECTION 16. OTHER INFORMATION**Further information**

Revision Date : 01/27/2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SUBMITTAL IDENTIFICATION SHEET

To be completed by Contractor/CM

WEBSTER UNIVERSITY ISB	
PROJECT NAME	
8274 BIG BEND BLVD	
ADDRESS	
NUMBER	
WEBSTER UNIVERSITY	
OWNER	
CANNON DESIGN	
ARCHITECT / ENGINEER	
DEVIN D GATES	
SUBMITTED BY	
075323-001	
CONTRACTOR / CM SUBMITTAL NO.	CANNON DESIGN SUBMITTAL NO.
	075323
DRAWING / DETAIL REFERENCE	SPECIFICATION SECTION / PARAGRAPH
MANUFACTURER / SUPPLIER	ITEM / PRODUCT ID
REQUIRED DATE	PRIORITY
	CRITICAL

ITEM BEING SUBMITTED (check only one)

- | | | |
|---|--|--|
| ☐ Shop Drawings | ☐ Certification / Qualifications | ☐ Coordination Drawing |
| ☐ Samples (____ copies) | ☐ Record Documents | ☐ Calculations |
| ☐ LEED Submittal | ☐ Product Data | ☐ Schedules |
| ☐ Other _____ | ☐ O&M Manuals | |

ITEM BEING SUBMITTED FOR (check only one)

- ☐ Action ☐ Information Only ☐ Record

REMARKS OR DEVIATIONS

Email correspondence with KWA provided clarifications for requested information and warranty letter attached.

CONTRACTOR / CM CERTIFICATION (SUBMITTALS NOT CERTIFIED WILL BE RETURNED WITHOUT REVIEW)



PARIC CORPORATION
SUBMITTAL STAMP

THIS SHOP DRAWING HAS BEEN REVIEWED BY PARIC CORPORATION

Subcontractor remains responsible for dimensions, quantities, coordination with other trades and compliance with contract documents.

By:

Devin D. Gates

DEVIN D GATES	10/11/16
REVIEWED BY	DATE

To be completed by Reviewer

07 5323-001 REV002
CANNON DESIGN SUBMITTAL NUMBER
10/11/16
RECEIVED DATE

- ☐ A. No Exceptions Taken
No further review of submittal is required.
- ☒ B. Make Corrections Noted
Incorporate corrections in work; resubmission is not required.
- ☐ C. Revise and Resubmit
Revise as noted, and resubmit for review.
- ☐ D. Rejected
Submittal is not in compliance with Contract Documents; provide new submittal.
- ☐ E. For Record / Information Only
Submittal was reviewed for Record / Information purposes only.
- ☐ F. Not Required for Review
Submittal is not required by Contract Documents and has not been reviewed.

Review is for conformance with the design concept of this project and for general compliance with contract documents. Contractor is responsible for quantities, dimensions and compliance with contract documents and for information that pertains to fabrication processes, construction techniques and coordination of this work with all trades which will be af
This review is null and void if submittal deviates from contra
and does not indicate or note deviations.

A/E COMMENTS

☐ See attached sheet(s) for additional comments

Final warranty must meet specification section 1.10. 2. requirements: wind speed coverage of that indicated on structural drawings (90 mph minimum), hail coverage for up to 2 inch diameter, and accidental puncture coverage of 16 man hours per year of warranty.
see comments below

Kathy Williams	10/11/16
REVIEWED BY	DATE

Gates, Devin

From: Scott Klingsick <scott@kwastl.com>
Sent: Friday, October 07, 2016 7:00 AM
To: Gates, Devin
Cc: kpatel@cannondesign.com
Subject: RE: Clarifications on returned EPDM shop drawings

Follow Up Flag: Follow up
Flag Status: Flagged

Yes this will be acceptable. We need the rest of the information revised and it to be resubmitted so we can approve submittal 075323-001. Thanks

Scott Klingsick, LEED Green Associate

Project Manager
9721 Litzsinger Rd.
St. Louis, MO 63124
(p) 314.962.2560 (f) 314.962.4057
scott@kwastl.com



KWA Architects

You have requested Kathy Williams and Associates, LLC dba KWA to supply electronic media containing plans for use by your company. Due to the potential that the information set forth on the electronic media can be modified, unintentionally or otherwise, the use of such electronic media will be at your company's sole risk and without any liability, risk or exposure to KWA LLC (Kathy Williams & Associates). You will not be automatically updated on revisions and/or modifications to the attached. **CONFIDENTIAL** The information, data and drawings embodied in this document are strictly confidential and are supplied with the understanding that they will not be disclosed to third parties without the prior written consent of the Owner.

From: Gates, Devin [mailto:ddgates@paric.com]
Sent: Thursday, October 06, 2016 4:59 PM
To: Scott Klingsick
Cc: kpatel@cannondesign.com
Subject: RE: Clarifications on returned EPDM shop drawings

Kelvin/Scott,

Were you able to take a look at this and does this resolve the impact resistance needs? I can resubmit formally as needed but with the back and forth I wanted to ensure we are all on the same page.

Thanks,

DEVIN GATES
SENIOR PROJECT ENGINEER

Cell: 314-348-8828
Main: 636-561-9500

- - - - -
77 Westport Plaza, Suite 250
St. Louis, MO 63146



Please consider your environmental responsibility before printing this e-mail

This e-mail message and any files transmitted with it may be CONFIDENTIAL and are intended for the addressee only. Any unauthorized use, dissemination of the information, or copying of this message is prohibited. If you are not the intended addressee, please notify the sender immediately and delete this message.

From: Aaron Hammerstone [<mailto:aaron.hammerstone@kirberg.com>]
Sent: Tuesday, October 04, 2016 7:10 AM
To: Gates, Devin; scott@kwastl.com
Cc: kpatel@cannondesign.com
Subject: FW: Clarifications on returned EPDM shop drawings

All,

Please see the two attachments, as well as the information in the below email in regards to the ASTM testing on JM EPDM membrane.

Thanks

Aaron Hammerstone | Project Manager

314.333.4710 Direct | aaron.hammerstone@kirberg.com

314.792.3777 Mobile

K I R B E R G C O M P A N Y

State-of-the Art Roofing and More. Since 1920.

1400 South Third Street Saint Louis, MO 63104
314.534.4444 Main | 314.534.2626 Fax

866.KIRBERG Toll-Free | <http://www.kirberg.com/>

Nationwide Service.
Founding Member of RoofConnect.
<http://www.roofconnect.com/>

***** NOTICE *****

The information contained in this e-mail, and in any accompanying documents, may constitute confidential and/or legally privileged information. The information is intended only for use by the designated recipient. If you are not the intended recipient (or responsible for the delivery of the message to the intended recipient), you are hereby notified that any dissemination, distribution, copying, or other use of, or taking of any action in reliance on this e-mail is strictly prohibited. If you have received this e-mail communication in error, please notify the sender immediately and delete the message from your system. All e-mail sent to and from this address will be received or otherwise recorded by the Kirberg Roofing, Inc e-mail system and is subject to archival, monitoring or review by, and/or disclosure to, someone other than the recipient.

From: Mark Tucker [<mailto:Mark@D7Reps.com>]
Sent: Monday, October 03, 2016 4:12 PM
To: Aaron Hammerstone

Cc: James Nunns; zac.stallings@jm.com; Jim Schriefer
Subject: RE: Clarifications on returned EPDM shop drawings

Aaron,

This JM EPDM 90NR data sheet shows we meet ASTM 4637 for EPDM. It's the same testing All EPDM is to meet, requiring minimum test results for numerous categories. There are three major manufacturers of EPDM: Johns Manville, Firestone, and Carlisle. NOTE: of the three, the latter two, have private label products, targeting a different market segment of contractors. The 3 major manufacturers are also, the only three members of the EPDM Roofing Association (ERA): <http://www.epdmroofs.org/about-era/members> . The goal of this organization is collectively establish current and accurate data documenting of EPDM.
<http://www.epdmroofs.org/about-era/who-we-are> .

Inside of **ASTM D 4637**, are individual tests for certain criteria. As a whole, make up ASTM D 4637.
Of which include the following:

ASTM D 5635 – Dynamic Puncture Resistance, 5J, Type 1 – Passes

ASTM D 5602 Static Puncture Resistance, 44.1 lbf, Type 1 – Passes

There are only two hail tests for the Single Ply Membranes (according to Jim D. Koontz- Crenshaw and Koontz).
Of which, the one most recognized, is FM's test, for approved Roof Nav assemblies per FM 4470.
For this project, we supplied the following two FM Nav #'s:

Assembly Properties

Assembly #:	392147-0-0	Slope:	1.0000
Roof System:	Single-Ply System	Wind Uplift*:	90
Application:	New Roof	Internal Fire:	1
Cover		Exterior Fire:	A
Securement:	Adhered		
Deck Type:	Steel	Hail:	SH
	For Use With Non-Combustible Walls:		No

AND

Assembly #:	374588-0-0	Slope:	1.0000
Roof System:	Single-Ply System	Wind Uplift*:	270
Application:	New Roof	Internal Fire:	NC
Cover		Exterior Fire:	A
Securement:	Adhered		
Deck Type:	Structural Concrete	Hail:	SH
	For Use With Non-Combustible Walls:		No

The roofing specification for this project, states in Part 1, paragraph 1.5, line 3, That the manufacturer must meet "Tested and listed by FM for class specified in "Performance Requirements" Article in Part 2 of this Section". In Part 2, **we met** Part 2, paragraph 2.2, A1. As noted, A2 criteria is for Modified Roofing. As such, A2 should be eliminated from requirements of the submittal, as **Part 2, 2.2, D.2** requires a Hail Resistance: SH. Of which, is met with both of the approved JOHNS MANVILLE Roof Nav Assembly numbers provided.

As for UL 2818, again is not a test used in the Single Ply industry. It is used primarily in the residential steep slope roofing market (shingles, tile, slate, metal roofs). The test requirement for this, is to test roof slopes at 6" in 12" or greater. This test was realized in 1996, by Major Property Insurers, the Institute of

Business and Home Safety (IBHS), and with United Laboratory. They developed ASMT 2218, to set a national standard, for roof impact resistance, for the residential steep slope market.

-
- A scope/ description, for the use of ASTM 2218, from the UL ASTM 2218 web page: <http://www.comm-2000.com/ProductDetail.aspx?UniqueKey=20884> click on "scope".
- 1 Scope

1.1 This test method provides impact resistance data for the evaluation of prepared roof covering materials. For purposes of this Standard prepared roof covering materials are considered to be small units, sheets or panels designed for installation with multiple layers of such materials installed in **overlapping rows normally on inclines exceeding 25 percent**.

We did a quick research of other manufacturers web sites, and on hand manufacturers data. Not one in the Single Ply manufacturing business, list or utilize the UL 2218 test. In fact, all manufacturers use the same testing, as it relates to the ASTM (see above for Static and Dynamic Puncturing) for that membrane. In this project instance, is EPDM (ASTM D 4637).

It appears to us, that there seems to be a mix of an EPDM specification, and a Modified/ Residential specification.

If this information does not satisfy the needs of the BID Documents, please let me know.

Mark

From: Aaron Hammerstone [<mailto:aaron.hammerstone@kirberg.com>]
Sent: Friday, September 30, 2016 2:25 PM
To: Mark Tucker <Mark@D7Reps.com>
Subject: Fwd: Clarifications on returned EPDM shop drawings

Thanks,

Aaron Hammerstone

Project Manager
Kirberg Company
(314)792-3777

Begin forwarded message:

From: Scott Klingsick <scott@kwastl.com>
Date: September 30, 2016 at 2:24:29 PM CDT
To: Aaron Hammerstone <aaron.hammerstone@kirberg.com>, "Gates, Devin" <ddgates@paric.com>
Cc: "Szachnieski, Jason" <JRSzachnieski@paric.com>, Kathy Williams <kathy@kwastl.com>
Subject: RE: Clarifications on returned EPDM shop drawings

Aaron,

Sorry for the confusion. The wrong ASTM number listed in the specification. It should have been ASTM D 4637-08 "Specification for EPDM Sheet Used in Single-ply Roof Membrane" and/or UL 2218 Standard for Impact Resistance of Prepared Roof Covering Materials. We need testing and product data to show compliance with the requirements impact resistance for the hail requirements on this project.

Scott Klingsick, LEED Green Associate

Project Manager
9721 Litzsinger Rd.
St. Louis, MO 63124
(p) 314.962.2560 (f) 314.962.4057
scott@kwastl.com



KWA Architects

You have requested Kathy Williams and Associates, LLC dba KWA to supply electronic media containing plans for use by your company. Due to the potential that the information set forth on the electronic media can be modified, unintentionally or otherwise, the use of such electronic media will be at your company's sole risk and without any liability, risk or exposure to KWA LLC (Kathy Williams & Associates). You will not be automatically updated on revisions and/or modifications to the attached. **CONFIDENTIAL** The information, data and drawings embodied in this document are strictly confidential and are supplied with the understanding that they will not be disclosed to third parties without the prior written consent of the Owner.

From: Aaron Hammerstone [<mailto:aaron.hammerstone@kirberg.com>]

Sent: Friday, September 30, 2016 12:13 PM

To: Gates, Devin; Scott Klingsick

Cc: Szachnieski, Jason

Subject: Re: Clarifications on returned EPDM shop drawings

ASTM D 3746 is for bituminous roofing. ASTM D 4272 is for plastic films.

This is an EPDM roof system. I think I'm missing something here.

Thanks,

Aaron Hammerstone

Project Manager
Kirberg Company
(314)792-3777

On Sep 30, 2016, at 11:26 AM, Gates, Devin <ddgates@paric.com> wrote:

Aaron,

See convo below regarding the shop drawing markups.

DEVIN GATES
SENIOR PROJECT ENGINEER

Direct: [636-561-9592](tel:636-561-9592)

Main: [636-561-9500](tel:636-561-9500)

Cell: [314-348-8828](tel:314-348-8828)

[77 Westport Plaza, Suite 250](#)
[St. Louis, MO 63146](#)

Sent from my iPhone

Begin forwarded message:

From: "Patel, Kelvin" <kpatel@CANNONDESIGN.COM>
Date: September 30, 2016 at 11:21:32 AM CDT
To: "Gates, Devin" <ddgates@paric.com>, "Szachnieski, Jason" <JRSzachnieski@paric.com>
Cc: "Grossman, Lynn" <lgrossman@CANNONDESIGN.COM>
Subject: FW: Clarifications on returned EPDM shop drawings

Devin,

See clarification from KWA below.

Thanks,

Kelvin Patel, CDT, LEED AP BD+C
Associate



T 314.425.8756

From: Scott Klingsick [<mailto:scott@kwastl.com>]
Sent: Friday, September 30, 2016 11:13 AM
To: Patel, Kelvin <kpatel@CANNONDESIGN.COM>; Kathy Williams <kathy@kwastl.com>
Cc: Grossman, Lynn <lgrossman@CANNONDESIGN.COM>
Subject: RE: Clarifications on returned EPDM shop drawings

Kelvin,

It is fine to show the building taller than 60' information.
We do need submittal for the 2.2 A.2. Impact
Resistance: Test reports and product data showing
compliance with ASTM D 3746 or ASTM D 4272. Thanks

Scott Klingsick, LEED Green Associate
Project Manager
9721 Litzsinger Rd.
St. Louis, MO 63124
(p) 314.962.2560 (f) 314.962.4057
scott@kwastl.com



You have requested Kathy Williams and Associates, LLC dba KWA to supply electronic media containing plans for use by your company. Due to the potential that the information set forth on the electronic media can be modified, unintentionally or otherwise, the use of such electronic media will be at your company's sole risk and without any liability, risk or exposure to KWA LLC (Kathy Williams & Associates). You will not be automatically updated on revisions and/or modifications to the attached. **CONFIDENTIAL** The information, data and drawings embodied in this document are strictly confidential and are supplied with the understanding that they will not be disclosed to third parties without the prior written consent of the Owner.

From: Patel, Kelvin [<mailto:kpatel@CANNONDESIGN.COM>]
Sent: Thursday, September 29, 2016 1:14 PM
To: Scott Klingsick; Kathy Williams
Cc: Grossman, Lynn
Subject: FW: Clarifications on returned EPDM shop drawings

Kathy / Scott,

Please review Paric's questions and provide comments.

Thanks,

Kelvin Patel, CDT, LEED AP BD+C

Associate



T 314.425.8756

From: Gates, Devin [<mailto:ddgates@paric.com>]
Sent: Thursday, September 29, 2016 1:04 PM
To: Patel, Kelvin <kpatel@CANNONDESIGN.COM>
Cc: Szachnieski, Jason <JRSzachnieski@paric.com>
Subject: Clarifications on returned EPDM shop drawings

Kelvin,

I have a couple of clarifications on two items from the attached rejected submittal.

1. On page 3 the perimeter and corner dimensions are crossed out for buildings taller than 60' however this building is higher than 60' in locations, is this note correct?
2. Can you please be more specific on what is being requested in the note "submit information for A2"? Johns Mansville did not feel like any of this section applies to the EPDM roof.

Thank you,

DEVIN GATES
SENIOR PROJECT ENGINEER

Cell: 314-348-8828
Main: 636-561-9500

77 Westport Plaza, Suite 250
St. Louis, MO 63146

PARIC.COM



Please consider your environmental responsibility before printing
this e-mail

This e-mail message and any files transmitted with it may be CONFIDENTIAL
and are intended for the addressee only. Any unauthorized use, dissemination
of the information, or copying of this message is prohibited. If you are not the
intended addressee, please notify the sender immediately and delete this
message.

<image005.png>

<image004.png>

<image005.png>

<image006.png>

<image007.jpg>