

Firestop Wrap Strip (CP 648-S)

Product description

- A single wrap strip of intumescent, flexible firestop for use with plastic and insulated pipe penetrations

Product features

- Highly intumescent
- Pre-measured — no cutting required
- Integrated fastening tape
- Cost effective
- Quick and easy closure without tools
- Ideal for very tight installations

Areas of application


- Firestopping combustible pipe penetrations
- Difficult applications where space is limited
- Penetrations through concrete over metal deck
- Suitable for the following plastic pipe materials: PVC, CPVC, ABS, FRPP

For use with

- Concrete, masonry, wood floor and gypsum wall assemblies
- Wall and floor assemblies rated up to 3 hours


Examples

- Waste water pipes
- Fresh water pipes
- Decking penetrations



Technical Data*	CP 648-S
Density	Approx. 1.35 g/cm³
Dimension (approximate) (thkns" x width" x length")	1.5": 3/16" x 1" x 6-3/4" 2": 3/16" x 1" x 8-1/4" 3": 3/16" x 1-3/4" x 11-1/2" 4": 3/8" x 1-3/4" x 15" 6": 1/2" x 1-3/4" x 22-1/4"
Color	Black with foil backing
Temperature resistance	-40°F to 212°F (-40°C to 100°C)
Intumescent activation	Approx. 320°F (160°C)
Expansion ratio (unrestricted)	1:40
Tested in accordance with	
• UL 1479 • ASTM E 814 • ASTM G21	

*At 73°F (23°C) and 50% relative humidity



Installation instructions for CP 648-S

Notice

- Before handling, read Material Safety Data Sheet and product label for safe usage and health information.
- Instructions below are general guidelines — always refer to the applicable drawing in the UL Fire Resistance Directory or Hilti Firestop Systems Guide for complete installation information

Installation

1. Clean the plastic or insulated pipe penetration. Expansion of the intumescent material during a fire closes the plastic pipe. Very dirty pipes (ie: with remains of mortar) may lead to a delay in the closing action. Soiled plastic or insulated pipes should, therefore, be cleaned in the area where the CP 648-S Firestop Wrap Strip is to be installed.
2. Install Wrap Strip. First check the annular space to ensure compatibility with the appropriate UL System. Use the CP 648-S Firestop Wrap Strip corresponding to the diameter of the pipe to be installed. Wrap the CP 648-S strip around the pipe and fasten it tightly using the integrated adhesive strip.

Push the CP 648-S Firestop Wrap Strip into the annular space in accordance with the UL listing.


3. Seal against smoke and gas. Seal the remaining gap with Hilti FS-ONE sealant.
4. For maintenance reasons, a penetration seal can be permanently marked with an identification plate and fastened in a visible position next to the seal.

Not for use


- In highly corrosive surroundings
- Outdoors

Storage


- Store only in the original packaging in a location protected from moisture at temperatures between 23°F and 86°F (-5°C and 30°C).




1. Clean penetration




2A. Wrap the CP 648-S Wrap Strip around the pipe and fasten it tightly with the adhesive strip.



2B. Push the CP 648-S Wrap Strip along the pipe and into the annular space as indicated above.



3. Seal penetration against smoke with FS-ONE sealant.



4. Fasten installation plate (if required)

Hilti. Outperform. Outlast.

Hilti, Inc. (U.S.) 1-800-879-8000 • www.us.hilti.com • en español 1-800-879-5000 • Hilti Firestop Systems Guide



Hilti Firestop
Saving lives
through innovation
and education

CERTIFICATE OF COMPLIANCE

Certificate Number 20160829-R13240
Report Reference R13240
Issue Date 2016-August-29

Issued to: Hilti Construction Chemicals, Div of Hilti Inc.
5400 S 122nd East Ave
Tulsa, OK 74146

**This is to certify that
representative samples of** Fill, Void or Cavity Materials
Fill, Void or Cavity Materials Certified for Canada

CP 648E and CP 648S (Product number may be suffixed to denote size) Wrap Strip for use in Through-Penetration Firestop Firestop Systems as currently described in the UL Fire Resistance Directory and in the Products Certified for Canada Directory.

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: ANSI/UL 1479, "Fire Tests of Through-Penetration Firestops,"
CAN/ULC-S115, "Standard Method of Fire Tests of Firestop Systems."

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>





September 24, 2015

To Whom It May Concern:

Re: **CP 648 E&S Firestop Wrap Strips – LEED Information**

Item Numbers:

304303	304307
304304	304308
304305	304309
304306	

The Hilti CP 648 E & S Firestop Wrap Strips are manufactured in Germany.

The Hilti CP 648 E & S Firestop Wrap Strips have a VOC content of 3.1 grams/liter.

The amount of post-consumer or post-industrial content in CP 648 E & S Firestop Wrap Strips is not known. The packaging is recyclable. The CP 648 E & S Firestop Wrap Strips do not contain any Rapidly Renewable Materials.

The CP 648 E & S Firestop Wrap Strips are not regulated as a hazardous waste by the Federal EPA Standards. The regulations for the disposal of non-regulated industrial waste can vary from state to state and even city to city. For this reason, you should consult your local and state regulatory agencies for direction on disposal.

Please feel free to contact me at (918) 872-3704 if you have questions.

Sincerely,

Jerry Metcalf MPH, CHMM
Sr. Manager, Safety/Environmental
Hilti Inc.
(918) 872 3704
jerry.metcalf@hilti.com

Rev. Date: 8/14/15

The manufacturing plant location on this certificate has been provided for LEEDS reporting purposes only. It should never be used for Country of Origin certification or a representation of compliance/non-compliance with Buy American or Buy America requirements, as those requirements differ.

The manufacturing plant location(s) identified on the certificate represent standard Hilti catalog products only. "Specially" produced non-catalog Hilti products may have differing manufacturing plant locations.

Contact your Hilti representative in cases of "specially" produced products for a custom LEEDS certificates.

Hilti, Inc.
5400 South 122nd East Avenue
Tulsa, OK 74146

1-800-879-8000
www.hilti.com

Shop Drawing Submittal Review

Transmitted To: Cannon Design

Date: May 1, 2017

Attention: stl-cac@cannondesign.com

Contact Person / WTA Field Inspector:
Patrick Garner

Project Name: Webster University-**ISB**

Reviewed by: Mike Nolte

Project No. WT 14127.01

☐

UPS

☐

Courier

☒

Email

Copies	No.	Description
1 PDF	078413 A01	(Submittal No. 07 8413-003))
		(Cannon #00000-004) - (Paric #15051-) – (WES #607)
		➤ Penetration Fire Stopping

Remarks: Architect to provide final review of submittal. Install per manufacturer's instructions to maintain fire rating of penetrated walls.

c: **Kelvin Patel**
Kpatel@cannondesign.com

☐

Furnish as Submitted

☐

Furnish as Noted

☐

Rejected

☐

Revise & Resubmit

☒

Reviewed

☐

Corrections or comments made on shop drawings during this review do not relieve contractor from compliance with requirements of drawings and specifications. This check is only for review of general conformance with the design concept of project and general compliance with information given in contract documents. Contractor is responsible for: confirming and correlating all quantities and dimensions; selecting fabrication processes and techniques of construction; coordinating his work with that of all other trades; and performing his work in a safe and satisfactory manner.

SUBMITTAL IDENTIFICATION SHEET

To be completed by Contractor/CM

PROJECT NAME	
ADDRESS	
NUMBER	
OWNER	
ARCHITECT / ENGINEER	
SUBMITTED BY	
CONTRACTOR / CM SUBMITTAL NO.	CANNON DESIGN SUBMITTAL NO.
DRAWING / DETAIL REFERENCE	SPECIFICATION SECTION / PARAGRAPH
MANUFACTURER / SUPPLIER	ITEM / PRODUCT ID
REQUIRED DATE	PRIORITY
CRITICAL	☐

To be completed by Reviewer

CANNON DESIGN SUBMITTAL NUMBER
RECEIVED DATE

- ☐ **A. No Exceptions Taken**
No further review of submittal is required.
- ☐ **B. Make Corrections Noted**
Incorporate corrections in work;
resubmission is not required.
- ☐ **C. Revise and Resubmit**
Revise as noted, and resubmit for review.
- ☐ **D. Rejected**
Submittal is not in compliance with Contract Documents;
provide new submittal.
- ☐ **E. For Record / Information Only**
Submittal was reviewed for Record / Information
purposes only.
- ☐ **F. Not Required for Review**
Submittal is not required by Contract Documents
and has not been reviewed.

Review is for conformance with the design concept of this project and for general compliance with contract documents. Contractor is responsible for quantities, dimensions and compliance with contract documents and for information that pertains to fabrication processes, construction techniques and coordination of this work with all trades which will be affected thereby. This review is null and void if submittal deviates from contract documents and does not indicate or note deviations.

ITEM BEING SUBMITTED (check only one)

- ☐ Shop Drawings ☐ Certification / Qualifications ☐ Coordination Drawing
☐ Samples ☐ Record Documents ☐ Calculations
 (_____ copies) ☐ Product Data ☐ Schedules
☐ LEED Submittal ☐ O&M Manuals
☐ Other

ITEM BEING SUBMITTED FOR (check only one)

- ☐ Action ☐ Information Only ☐ Record

REMARKS OR DEVIATIONS

CONTRACTOR / CM CERTIFICATION
(SUBMITTALS NOT CERTIFIED WILL BE RETURNED WITHOUT REVIEW)



PARIC CORPORATION
SUBMITTAL STAMP

THIS SHOP DRAWING HAS BEEN REVIEWED BY PARIC CORPORATION

Subcontractor remains responsible for dimensions, quantities, coordination with other trades and compliance with contract documents.

Ry:

By:
Devin D. Gates

REVIEWED BY	DATE

A/E COMMENTS

- ☐
- See attached sheet(s) for additional comments

REVIEWED BY	DATE



77 Westport Plaza
Suite 250
St. Louis, MO 63146

TRANSMITTAL

No. 15051-0557

Paric Corporation

PROJECT: 15051-Webster University Interdisciplinary Science Building

DATE: 04/19/2017

TO: Cannon Design
1100 Clark Ave
St Louis MO 63102

Fax;
314-241-2203

RE: Penetration Fire Stopping Product Data

ATTN: Kelvin Patel

JOB: 15051

WE ARE SENDING:	SUBMITTED FOR:	ACTION TAKEN:
☐ Shop Drawings	☒ Approval	☐ Approved as Submitted
☐ Letter	☐ Your Use	☐ Approved as Noted
☐ Prints	☐ As Requested	☐ Returned After Loan
☐ Change Order	☐ Review and Comment	☐ Resubmit
☐ Plans		☐ Submit
☐ Samples	SENT VIA:	☐ Returned
☐ Specifications	☐ Attached	☐ Returned for Corrections
☒ Other: Product Data	☐ Separate Cover Via:	☐ Due Date:

<i>Item</i>	<i>Package</i>	<i>Code</i>	<i>Rev.</i>	<i>Copies</i>	<i>Date</i>	<i>Description</i>	<i>Status</i>
Submittal		078413-003	1		04/19/2017	Penetration Fire Stopping Product Data	Submitted

NOTES:

CC:

Signed: _____
Devin Gates



Mechanical

LETTER OF TRANSMITTAL

TO: Paric Corporation

77 West Port Plaza #250

St. Louis, MO 63146

ATTN: Jason Szachnieski, Devin Gates

DATE: 3/16/17

JOB #: 5768

RE: Webster ISB

We are sending you

☒

Shop drawings

☐ Attached

☐ Prints

☐ Under separate cover

☐ Plans

☐ Samples

☐ Specifications

☐ Copy of letter

☐ Change order

☐ Other

COPIES	DATE	NO.	DESCRIPTION
1	3/16/17	078413	Penetration Fire Stopping

These are transmitted as checked below:

☐ For signature

☐ For your use

☐ As requested

☐ For bids due

☒

For review and comment

☐ Approved as submitted

☐ Approved as noted

☐ Returned for corrections

☐ Prints returned after loan to us

☐ Other

☐ Resubmit

☒

Submit

☐ Return

☐ copies for approval

☐ copies for distribution

☐ corrected prints

Remarks: Please return by 3/23/16

COPY TO: file

SIGNED:

Alex Chambers



Mechanical

Webster University ISB Webster Groves, MO

Submittal #:

078413

Submittal Description:

Penetration Fire Stopping

Return By:

3/23/17

Please Note: To avoid scheduling delays and equipment release delays, please submit by the "Return By" date.

CHECKED BY:			
DESIGNER:		ENGINEER:	
☒	NO EXCEPTION TAKEN	☐	MAKE CORRECTIONS NOTED
☐	SUBMIT SPECIFIED ITEM	☐	REVISE AND RESUBMIT
☐	REJECTED	☐	
Checking is only for general conformance with the design concept of the project and general compliance with the information given in the contract documents. Any action shown is subject to the requirements of the plans and specifications. Equipment supplier is responsible for: dimensions which shall be confirmed and correlated at the job site; fabrication processes and techniques of construction; coordination of his work with that of all other trades; and satisfactory performance of his work.			
		Job #:	5768
		Date:	3/16/17
		By:	ARC